

OMV ATF M plus is a modern, red coloured multifunctional transmission fluid produced from synthetic base fluids and carefully selected additives for highest shift comfort in automatic transmissions of passenger cars and SUV of MERCEDES BENZ.

Properties

The extremely high viscosity index of this special oil provides excellent viscosity - temperature behaviour and thus grants applicability in a wide temperature range. OMV ATF M plus shows outstanding aging stability and anti-foam behaviour, excellent flow properties and protects reliably from wear and corrosion.

Additionally, OMV ATF M plus provides high fuel efficiency potential and a very stable coefficient of friction, which leads to excellent gear shift comfort over the entire transmission service life.

Application

OMV ATF M plus was developed especially for MERCEDES-BENZ 7-gear automatic transmission (NAG 2, Typ 722.9). OMV ATF M plus is backwards compatible to all 5-gear automatic transmissions (Typ 722.6) and is suitable for older automatic transmissions to increase the shift comfort.

Exceeds

Allison C-4, CATERPILLAR TO-2

Approval

MB 236.14

Technical data (typical values)

Property	Unit	OMV ATF M plus
Density @ 15°C	Kg/m ³	850
Flash point COC	°C	200
Viscosity @ -40°C	mPas	8.500
Viscosity @ 40°C	mm ² /s	26.9
Viscosity @ 100°C	mm ² /s	6.5
Viscosity Index	---	210
Pour point	[°C]	<-51

Safety, health, environment

A data sheet with safety and health information can be found on the Internet at www.omv.com.

Used lubricants and empty containers must be disposed of in accordance with environmental regulations.